


## DGP M 255 FM (961 105)


- Discharge capacity up to 100 kA (10/350  $\mu$ s)
- Total current arrester specifically designed for installation in "3+1" and "1+1" circuits of TT systems according to IEC 60364-5-53 between neutral conductor N and protective conductor PE
- Creepage discharge spark gap technology



Figure without obligation



Basic circuit diagram DGP M 255 FM



Dimension drawing DGP M 255 FM

Coordinated modular single-pole N-PE lightning current arrester for  $U_c = 255$  V; also available with remote signalling contact for the monitoring system (floating changeover contact)

Type	DGP M 255 FM
Part No.	961 105
SPD according to EN 61643-11	Type 1
SPD according to IEC 61643-1/-11	Class I
Max. continuous operating a.c. voltage ( $U_c$ )	255 V
Lightning impulse current (10/350 $\mu$ s) ( $I_{imp}$ )	100 kA
Specific energy (W/R)	2.50 MJ/ohms
Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	100 kA
Voltage protection level ( $U_p$ )	$\leq 1.5$ kV
Follow current extinguishing capability a.c. ( $I_{ri}$ )	100 A <sub>rms</sub>
Response time ( $t_A$ )	$\leq 100$ ns
Temporary overvoltage (TOV)	1200 V / 200 ms
TOV characteristic	withstand
Operating temperature range (parallel connection) ( $T_{UP}$ )	-40°C...+80°C
Operating temperature range (series connection) ( $T_{US}$ )	-40°C...+60°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (N, PE, $\pm$ ) (min.)	10 mm <sup>2</sup> solid/flexible
Cross-sectional area (N, PE) (max.)	50 mm <sup>2</sup> stranded/35 mm <sup>2</sup> flexible
Cross-sectional area ( $\pm$ ) (max.)	35 mm <sup>2</sup> stranded/25 mm <sup>2</sup> flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Approvals	VDE, KEMA, UL
Type of remote signalling contact	changeover contact
a.c. switching capacity	250 V/0.5 A
d.c. switching capacity	250 V/0.1 A; 125 V/0.2 A; 75 V/0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm <sup>2</sup> solid/flexible
Weight	320 g
Customs tariff number	85363010
GTIN	4013364118683
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.