


DV M TT 2P 255 FM (951 115)


- Prewired spark-gap-based combined lightning current and surge arrester consisting of a base part and plug-in protection modules
- Maximum system availability due to RADAX Flow follow current limitation
- Capable of protecting terminal equipment



Figure without obligation



Basic circuit diagram DV M TT 2P 255 FM



Dimension drawing DV M TT 2P 255 FM

Modular combined lightning current and surge arrester for single-phase TT and TN systems ("1+1" circuit)

Type	DV M TT 2P 255 FM
Part No.	951 115
SPD according to EN 61643-11 / IEC 61643-1/-11	Type 1 / Class I
Energy coordination with terminal equipment	Type 1 + Type 2
Energy coordination with terminal equipment ($\leq 5\text{m}$)	Type 1 + Type 2 + Type 3
Nominal a.c. voltage (U_N)	230 V
Max. continuous operating a.c. voltage (U_C)	255 V
Lightning impulse current (10/350 μs) [L+N-PE] (I_{total})	50 kA
Specific energy [L+N-PE] (W/R)	625.00 kJ/ohms
Lightning impulse current (10/350 μs) [L-N]/[N-PE] (I_{imp})	25 / 50 kA
Specific energy [L-N]/[N-PE] (W/R)	156.25 kJ/ohms / 625.00 kJ/ohms
Nominal discharge current (8/20 μs) (I_n)	25 / 50 kA
Voltage protection level [L-N]/[N-PE] (U_p)	$\leq 1.5 \text{ kV} / \leq 1.5 \text{ kV}$
Response time (t_A)	$\leq 100 \text{ ns}$
Follow current extinguishing capability [L-N]/[N-PE] (I_n)	50 kA _{rms} / 100 A _{rms}
Follow current limitation/Selectivity	no tripping of a 20 A gL/gG fuse up to 50 kA _{rms} (prosp.)
Max. backup fuse (L) up to $I_K = 50 \text{ kA}_{\text{rms}}$	315 A gL/gG
Max. backup fuse (L-L')	125 A gL/gG
Temporary overvoltage (TOV) [L-N] (U_T)	440 V / 5 sec.
Temporary overvoltage (TOV) [N-PE] (U_T)	1200 V / 200 ms
TOV characteristic	withstand
Operating temperature range [parallel]/[series] (T_U)	-40°C...+80°C / -40°C...+60°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (L, L', N, N', PE, \neq) (min.)	10 mm ² solid/flexible
Cross-sectional area (L, N, PE) (max.)	50 mm ² stranded/35 mm ² flexible
Cross-sectional area (L', N', \neq) (max.)	35 mm ² stranded/25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94-V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Approvals	KEMA, VDE, UL, VdS
Type of remote signalling contact	changeover contact
a.c. switching capacity	250 V/0.5 A
d.c. switching capacity	250 V/0.1 A; 125 V/0.2 A; 75 V/0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm ² solid/flexible
Extended technical data:	Use in installations with prospective short-circuit currents of more than 50 kA_{rms} (tested by VDE)
- Maximum prospective short-circuit current	100 kA _{rms} (220 kA _{peak})
- Limitation/extinction of mains follow currents	up to 100 kA _{rms} (220 kA _{peak})
- Max. backup fuse (L) up to $I_K = 100 \text{ kA}_{\text{rms}}$	315 A gL/gG
Weight	664 g
Customs tariff number	85363030
GTIN	4013364108127
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.