


DR M 4P 255 (953 400)


- Four-pole surge arrester consisting of a base element and plug-in protection module
- High discharge capacity due to heavy-duty zinc oxide varistor/spark gap combination
- Energy coordination with other arresters of the Red/Line product family



Figure without obligation



Basic circuit diagram DR M 4P 255



Dimension drawing DR M 4P 255

Four-pole surge arrester consisting of a base part and plug-in protection module; FM version with floating remote signalling contact

Type	DR M 4P 255
Part No.	953 400
SPD according to EN 61643-11	Type 3
SPD according to 61643-1/-11	Class III
Nominal a.c. voltage (U_N)	230/400 V
Max. continuous operating a.c. voltage (U_C)	255/440 V
Nominal load current a.c. (I_L)	25 A
Nominal discharge current (8/20 μ s) (I_n)	3 kA
Total discharge current (8/20 μ s) [L1+L2+L3+N-PE] (I_{total})	8 kA
Combined impulse (U_{OC})	6 kV
Combined impulse [L1+L2+L3+N-PE] ($U_{OC total}$)	16 kV
Voltage protection level [L-N] (U_P)	≤ 1000 V
Voltage protection level [L/N-PE] (U_P)	≤ 1500 V
Response time [L-N] (t_A)	≤ 25 ns
Response time [L/N-PE] (t_A)	≤ 100 ns
Max. mains-side overcurrent protection	25 A gL/gG or B 25 A
Short-circuit withstand capability for mains-side overcurrent protection with 25 A gL/gG	6 kA _{rms}
Temporary overvoltage (TOV) [L-N] (U_T)	335 V / 5 sec.
Temporary overvoltage (TOV) [L/N-PE] (U_T)	400 V / 5 sec.
Temporary overvoltage (TOV) [N-PE] (U_T)	1200 V / 200 ms
TOV characteristic [L-N]	withstand
TOV characteristic [L/N-PE]	withstand
TOV characteristic [L+N-PE]	safe
Operating temperature range (T_U)	-40°C...+80°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	0.5 mm ² solid/flexible
Cross-sectional area (max.)	4 mm ² stranded/2.5 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 modules, DIN 43880
Approvals, Certifications	KEMA, VDE, UL
Weight	138 g
Customs tariff number	85363010
GTIN	4013364115767
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.