


BXT ML4 BC 5 (920 350)

- LifeCheck SPD monitoring function
- Optimal protection of max. four lines
- For installation in conformity with the lightning protection zones concept at the boundaries from 0_{A-2} and higher



Figure without obligation



Basic circuit diagram BXT ML4 BC 5



Dimension drawing BXT ML4 BC 5

Space-saving combined lightning current and surge arrester module with LifeCheck feature for protecting max. four unearthed single lines with common reference potential. If LifeCheck detects thermal or electrical overload, the arrester has to be replaced. This status is indicated contactlessly by the DEHNrecord LC / MCM reader.

Type	BXT ML4 BC 5
Part No.	920 350
SPD class	TYPE 1 Pt
SPD monitoring system	LifeCheck
Nominal voltage (U_n)	5 V
Max. continuous operating d.c. voltage (U_c)	6.0 V
Max. continuous operating a.c. voltage (U_c)	4.2 V
Nominal current at 45°C (I_t)	1.0 A
D1 Total lightning impulse current (10/350 μ s) (I_{imp})	10 kA
D1 Lightning impulse current (10/350 μ s) per line (I_{imp})	2.5 kA
C2 Total nominal discharge current (8/20 μ s) (I_n)	20 kA
C2 Nominal discharge current (8/20 μ s) per line (I_n)	10 kA
Voltage protection level line-line for I_{imp} D1 (U_p)	≤ 25 V
Voltage protection level line-PG for I_{imp} D1 (U_p)	≤ 550 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 9 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 550 V
Series resistance per line	1.0 ohm(s)
Cut-off frequency line-line (f_c)	1.0 MHz
Capacitance line-line (C)	≤ 5.4 nF
Capacitance line-PG (C)	≤ 16 pF
Operating temperature range	-40°C...+80°C
Degree of protection (with plugged-in protection module)	IP 20
Pluggable into	base part
Earthing via	base part
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21, UL 497B
SIL classification	SIL2 / SIL3 ^{*)}
ATEX approvals	DEKRA 11ATEX0089 X: II 3 G Ex nA IIC T4 Gc
IECEx approvals	DEK 11.0032X: Ex nA IIC T4 Gc
CSA & USA Hazloc approvals (1)	2516389: Class I Div. 2 GP A, B, C, D T4
CSA & USA Hazloc approvals (2)	2516389: Class I Zone 2, AEx nA IIC T4
Approvals	CSA, VdS, GOST
Weight	24 g
Customs tariff number	85363010
GTIN	4013364109131
PU	1 pc(s)

^{*)} For more detailed information, please visit www.dehn.de/en/sil/

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.