


USD 25 V24 HS S B (924 046)


- Plug-in surge arrester with two-stage protective circuit
- For installation in conformity with the lightning protection zones concept at the boundaries from $0_B - 2$ and higher



Figure without obligation



Basic circuit diagram USD 25 V24 HS S B



Dimension drawing USD 25 V24 HS S B

Energy-coordinated two-stage arrester for V.24 interfaces with handshake. 25-pin D-SUB version.

Type	USD 25 V24 HS S B
Part No.	924 046
SPD class	TYPE 2 Pt
Nominal voltage (U_N)	12 V
Max. continuous operating d.c. voltage (U_c)	12.5 V
C2 Nominal discharge current (8/20 μ s) line-PG (I_n)	2.5 kA
C2 Nominal discharge current (8/20 μ s) SG-PG (I_n)	7.5 kA
Voltage protection level line-SG for I_n C2 (U_p)	≤ 27 V
Voltage protection level SG-PG/line-PG for I_n C2 (U_p)	≤ 330 V
Voltage protection level line-SG at 1 kV/ μ s C3 (U_p)	≤ 18 V
Voltage protection level SG-PG at 1 kV/ μ s C3 (U_p)	≤ 220 V
Series resistance per line	15 ohms
Operating temperature range	-40°C...+80°C
Connection (input/output)	D-SUB 25 plug / D-SUB 25 socket
Pinning	line: 2/3/4/5/6/8/20, SG: 7, PG: 1
Earthing via	earthing screw or DIN rail
Test standards	IEC 61643-21 / EN 61643-21
Approvals	GOST
Weight	151 g
Customs tariff number	85363010
GTIN	4013364058774
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.