


## EXFS L300 (923 062)


- For indirect connection/earthing of functionally isolated parts of installations under lightning conditions
- For lightning equipotential bonding according to IEC 62305 in hazardous areas (zone 2)
- Approval according to ATEX directive 94/9/EC and IECEx



Figure without obligation



Installation of EXFS L300



Dimension drawing EXFS L300

Ex isolating spark gap for aboveground installation

Type	EXFS L300
Part No.	923 062
Lightning impulse current (10/350 $\mu$ s) ( $I_{imp}$ )	50 kA
Class of lightning current carrying capability acc. to EN 50164-3	N
Nominal discharge current (8/20 $\mu$ s) current (8/20) ( $I_n$ )	100 kA
Rated power-frequency withstand voltage (50 Hz) ( $U_{wAC}$ )	300 V
Lightning impulse sparkover voltage ( $U_{f,imp}$ )	$\leq 2.5$ kV
Power frequency sparkover voltage (50 Hz) ( $U_{sw}$ )	$\leq 1.2$ kV
Operating temperature range ( $T_U$ )	-20°C...+80°C
Degree of protection	IP 54
ATEX approvals	DEKRA 11ATEX0146 X
Ex marking according to EN 60079-0 and EN 60079-15: gas	II 3 G Ex nC IIC T4 Gc
IECEx approvals	IECEx DEK 11.0063X
Ex marking according to EN 60079-0	Ex nC IIC T4 Gc
Enclosure length	90 mm
Enclosure diameter	63 mm
Enclosure material	zinc die-cast, plastic
Connecting cable	H01N2-D 25 mm <sup>2</sup> with cable lug and screw/nut (M10)
Cable length	300 mm
Suitable for flange size	220-320 mm
Weight	733 g
Customs tariff number	85369085
GTIN	4013364038912
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.